

# DXC-5000

## High Capacity Hybrid Cross-Connect



- High density Ethernet/SDH/SONET
- MPLS-TP and Traffic-Engineered Pseudowires
- Synchronization: BITS, SyncE
- High capacity: STM-64/OC-192, 10 GbE
- Sub-50ms protection: 1:1, BLSR, PW, ERPS
- Carrier Ethernet: CE 2.0 Certified
- Optional TDM circuit emulation

DXC-5000 balances TDM and packet transport in a way unique to the industry. Its hybrid architecture allows for three transport modes: TDM-over-packet transport, hybrid TDM and packet transport, and all packet transport, based on identical hardware, software and features. This flexibility creates a unique opportunity for network designs, by optimizing every service based on the service requirements, without the limitations of a particular technology. In addition, DXC-5000 reduces operations costs by using a single platform for these service requirements and avoiding the need for multiple devices at any site.

When compared to the life cycle costs of separate TDM and packet networks, DXC-5000 reduces power consumption, software costs, training costs and the number of modules. Network utilization is also improved by using the full bandwidth of the packet and TDM transport.

Packet and E1/T1 services can be transported over Ethernet or SDH/SONET. Since each slot can directly access the Packet and TDM switches at the same time, services can be matched to best technology whether that is maximizing efficiency with statistical multiplexing or minimizing latency. This slot flexibility has the benefit that each port on each module can be individually routed via software to the appropriate switch reducing operations costs.

DXC-5000's transport flexibility ensures the lowest transport cost per bit. With the ability to perform statistical multiplexing, low cost TDM switching and DWDM in the same device, new services can use the lowest cost infrastructure across the entire network.

By matching the service interface to the best switch and the best transport method (Ethernet or SDH/SONET), each service can be delivered with the lowest latency required.

### ETHERNET

DXC-5000 provides best-in-class packet switching to create networks with the highest performance. Ingress rate limiting prevents any service or application from congesting/choking the network. Each packet is classified so that the appropriate network policies (like prioritization and scheduling) can be applied. Eight CoS queues and scheduling algorithms ensure that there are sufficient resources available to manage the data traffic efficiently. Standard G.8032 ERPS (Ethernet Ring Protection Switching) provides sub-50ms protected packet rings for greater resiliency. Multiple ringlets and multiple ring topologies are supported.

Ethernet OAM allows real-time monitoring of end-to-end circuits, connections or trunks, enabling quick detection and isolation of faults to a particular subnet, trunk, link or node. DXC-5000 features BFD-based Fault OAM and ping/traceroute at tunnel/pseudowire level. For 802.1q/802.1ad-based MEF services, DXC-5000 supports Y.1731/802.1ag-based CFM OAM (Port level down MEP) and Y.1731 PM counters.

# DXC-5000

## High Capacity Hybrid Cross-Connect

### CIRCUIT EMULATION

Even though many services and applications move from TDM to packet, a few TDM circuits will remain in the network. Circuit emulation provides an alternative transport method using an all Packet Transport Network. DXC-5000 employs E1/T1 SAToP and STM-1/OC-3 CEP for carrying this traffic with the reliability and protection mechanisms of legacy TDM networks, including card level protection for E1/T1 interfaces.

### OTN

DXC-5000 uses OTN technology to increase optical span length with Forward Error Correction (FEC), optimize bandwidth utilization for high bandwidth Ethernet requirements and reduce latency in networks with many nodes. OTN switching reduces the cost of high-speed transport throughout the network and DXC-5000 provides the aggregation/on-ramp to the OTN core network.

### SDH/SONET

Featuring a complete suite of SDH/SONET capabilities, DXC-5000 provides the reliability and performance expected of your transport network: predictable latency, low protection switching times, deterministic routes and manageable bandwidth.

### MPLS-TP

MPLS label-based Connection Oriented Ethernet allows packet traffic to be easily and precisely routed through the network. DXC-5000 provides MPLS-TP-based pseudowires for traffic engineered flows on trunks, which optimizes the network by providing the right amount of control.

The cost benefits of statistical multiplexing are combined with traffic engineering and capacity planning to lower CAPEX by right sizing the network. OPEX reductions come through faster provisioning, robust protection and quicker root cause analysis during failures. In addition, with mesh protection capabilities latency and protection switch times are minimized.

### SYNCHRONIZATION

SyncE , DCR, ACR

### ARCHITECTURE

DXC-5000 has a flexible architecture that allows it to build the network best suited for all services:

- Linear for rapid deployment
- Hub and spoke for cost effective buildouts at the edge of the network
- Ring and ringlet for high utilization and resiliency
- Meshed for low latency and flexible protection.

This is achieved with a unique combination of functionalities, including the ability for every optical port to be defined as a User to Network Interface (UNI) or a Network to Network Interface (NNI).

The DXC-5000 family includes the following members:

- DXC-5000-7 – Up to 5 tributary and 2 aggregation slots
- DXC-5000-7 with Expansion– Up to 10 tributary and 2 aggregation slots
- DXC-5000P –Non-modular device with predefined assembly options.

The assembly options of DXC-5000P are as follows:

- 8xGE optical + 8xGE electrical
- 4x10GE optical + 8xGE optical + 8xGE electrical
- 8xGE optical + 8xGE electrical + 16xE1/DS1 + 4xSTM1/OC3 CEM
- 4x10GE + 8xGE optical + 8xGE electrical + 16xE1/DS1 + 4xSTM1/OC3 CEM.

### MANAGEMENT AND SECURITY

Point and click technologies for Ethernet and SDH/SONET traffic allow for more accurate service designs, more efficient routing and better fault correlation. Accurate alarming and “fault to affected service mapping” enable fault resolution prioritization. Enhanced network element backups and simple remote software upgrades reduce operational costs while enhancing reliability. NMS server redundancy and geographical diversity ensure faster disaster recovery.



# DXC-5000

## High Capacity Hybrid Cross-Connect

### Ethernet Switch Capacity

Up to 64 Gbps bidirectional

### Interfaces to Ethernet Switch

10 GbE – up to 4 XFP

1 GbE – up to 24 ports

FE (10/100baseT) – up to 24 ports

### OPTICS

SFP and XFP

Tunable XFP

FEC for 10G and 622M ports

### RESILIENCY

#### TDM

Unprotected, 1+1 APS

UPSR, BLSR, 2F MS-SPRing

1:N line protection

1:1 E3/T3 protection

1:N E1/T1 protection

#### Ethernet

Ethernet ring protection ITU-T G.8032

1:1 bidirectional linear protection LSP

(RFC6378)

Link Aggregation Group (LAG)

Port mirroring and loopback

### MANAGEMENT

Web-based GUI

End to End Network Management

SNMPv3

### CIRCUIT EMULATION

E1: SAToP RFC4553/MEF8

T1: SAToP RFC4553/MEF8

### TIMING AND SYNCHRONIZATION

SyncE , DCR, ACR

### GENERAL

#### Physical (W x H x D)

444 mm x 88 mm x 235 mm (base chassis)

444 mm x 220 mm x 235 mm (with expansion)

ETSI and 23" rack mount options

#### Power Supply (Optional Redundancy)

-36V to -60V DC

230V AC, 50Hz

120V AC, 60Hz

#### Power Consumption

300W max

#### Environment

Operating Temperature: 0°C to 50°C

Relative Humidity: 10% to 90%, non-condensing

## DXC-5000

## High Capacity Hybrid Cross-Connect

Table 1. DXC-5000 Aggregation and Tributary Modules

Module	Description	Power Consumption	
Aggregation Modules			
	<b>Aggregate interface</b>	<b>Tributary interface</b>	
XA10G	1xSTM-4/16/OC-12/OC-48	2xSTM-1/OC-3	25 W
XA20G (SDH only)	1xSTM-16 Agg with + 1xSTM-4/1	2xSTM-1	30 W
	2xSTM-16 Agg		
XA60G	1xSTM-64/OC-192/OTU2	2xSTM-16/4/OC-48/12/OTU1/GE	70 W
		2xSTM-4/1/OC-12/3GE	
Tributary Modules			
ST6E3	DS3/E3		8.5 W
SOT18	8xSTM-1/OC-3 or 2xSTM-4/OC-12 or 1xSTM-16/OC-48		17 W
ST63xE1	63 *E1/T1		8.5 W
CEF-1	2xGE SFP + 1x1000 + 3x10/100		30 W
CEF-1-9P	1xGE SFP + 4x1000 + 4x10/100 (SDH Only)		30 W
CEL-5	2xGE SFP + 2x1000 + 4x10/100		28 W
CEL-6	8xGE SFP		32 W
CEF-4 (Switch)	2x 10GE XFP 2x GE SFP		80 W
Tributary Modules (Circuit Emulation Only)			
ST24DS3	24*DS3/E3		28 W
ST63DS1CEM	63 *E1/T1		24 W
CEM1	8*SFP (STM-1/4/16/OC-3/12/48)		70 W
Tributary Modules (Expansion/Protection chassis)			
S63EIO	63E1/DS1 I/O ports for DXC5000 Expansion/Protection chassis		16 W
S63EWP	63E1/DS1 WP ports for DXC5000 Expansion/Protection chassis		16 W
S12E3IO	12 E3/DS3 ports for DXC5000 Expansion/Protection chassis		18 W
S12E3WP	12 E3/DS3 ports for DXC5000 Expansion/Protection chassis		18 W

## Ordering

Please contact your Regional Sales Manager

### International Headquarters

24 Raoul Wallenberg Street  
Tel Aviv 69719, Israel  
Tel. 972-3-6458181  
Fax 972-3-6498250, 6474436  
E-mail market@rad.com

### North America Headquarters

900 Corporate Drive  
Mahwah, NJ 07430, USA  
Tel. 201-5291100  
Toll free 1-800-4447234  
Fax 201-5295777  
E-mail market@radusa.com

[www.rad.com](http://www.rad.com)

Order this publication by Catalog No. 805086  
Order from: Cutter Networks Phone: 727-398-5252



[www.bestdatasource.com](http://www.bestdatasource.com)